

AY-Q6350

Anti- Vandal Mifare® Contactless
Smartcard Reader with Keypad



THIS ANTI-VANDAL MIFARE® 13.65 MHz SMARTCARD AND PIN CODE READER HAS AN ELEGANT DESIGN WITH BLUE BACKLIT KEYS. THE AY-Q6350 IS AN ADVANCED MODEL WITH MULTI-FORMAT OUTPUTS FOR HIGH COMPATIBILITY WITH STANDARD HOST ACCESS CONTROLLERS. IT HAS A LOCAL MENU TO PROGRAM FACILITY CODE AS WELL AS CARD & PIN CREDENTIAL MODES.

GENERAL DESCRIPTION

The AY-Q6350 is the latest addition to Rosslare's family of Mifare® card readers. It can read Mifare® card serial number (CSN) from all ISO 14443A-3 type cards. AY-Q6350 has locally programmable modes for 1- to 8-digit PIN codes, with a high-security option of "PIN plus card", as well as a 3-digit Facility code. Even with the unit's strong features, this reader is user-friendly and easy-to-install with an additional level of security in the form of a password-protected menu. This reader supports Wiegand 26-, 32-, 34-, and 40-Bit or Clock & Data output protocols. It has a 6-wire shielded cable interface to the host controller for power, data, LED control input, and tamper status. Backlight offers a higher level of user accessibility. This anti-vandal unit is ideal for installations where style, security and functionality are highly important.

MAIN FEATURES

- Incorporates the ISO-14443A (Mifare®) ID Format Protocol
- Read range of up to 45 mm (1.8 in.)
- 8 programmable proximity card transmission formats, Wiegand 26- to 40-Bit or Clock & Data

- Blue backlit 3x4 keypad
- High strength design, epoxy potted, fully sealed within an all-metallic housing
- Selectable LED control or buzzer control functions
- Made from tough polycarbonate plastic for improved performance in all weather conditions

PROFESSIONAL GRADE FEATURES

- Optical tamper sensor for cover and wall tamper detection
- 8 programmable PIN transmission formats for data and credential entry options
- Card + PIN mode for higher security
- Door bell key feature (from "*" key when interfaced with Rosslare controllers)
- Water-resistant with epoxy potting (IP65) suitable for indoor and outdoor applications
- One tri-colored LED and integral sounder for programming and operation
- Programmable Facility code
- Installation kit includes template label, security screw, and tool
- 60 cm (23.6 in.) 6-wire interface cable

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	5 to 16 VDC – from a linear type power supply (18 VDC is absolute maximum)
■ Standby Input Current	115 mA
■ Maximum Input Current	160 mA
■ LED Control	Dry Contact, N.O.
■ Proximity Card Reader	Max. read range: 44 mm (1.77in.) Operating Frequency: 13.56 MHz Compatible Cards: Mifare® Compatible ISO-14443A
■ Tamper Output	Open Collector, active low, maximum sink current 16mA

OPERATIONAL SPECIFICATIONS

■ Keypad	3x4 blue backlit keys for PIN codes entry and local programming Door bell key (*) function (with Rosslare controllers only)
■ Facility Code	Programmable
■ PIN Code Formats	8 selectable formats, from single to 8-digit PIN codes
■ Card Output Formats	8 selectable formats: Wiegand 26-Bit, with Facility code, 32-Bit, 32-Bit Reversed, 34-Bit, 40-Bit, Clock & Data and Wiegand Card + PIN
■ Indications and Sounds	Tri-colored LED, built-in sounder with selectable LED/sounder control input

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Indoor and outdoor use (all weather) – meets IP65
■ Operating Temperature	-31°C to 63°C (-25°F to 145° F)
■ Operating Humidity	0% to 95% (non-condensing)
■ RFI Protection	> 20 V/m up to 1000 MHz

PHYSICAL SPECIFICATIONS

■ Dimensions (H x W x D)	120 x 76 x 22mm (4.72 x 3 x 0.97 in.)
■ Weight	440 g (0.97 lb)

SYSTEM COMPONENTS

The AY-Q6350 is compatible with a variety of Rosslare's controllers (AC-225, AC-215, AC-115, and so on), as well as with many third-party systems. In addition, it is compatible with Rosslare's AT-T511, AT-T521 and AT-T531 Ultralight (64 bytes), 1K and 4K Mifare® cards.

PRODUCT WARRANTY

5-Year Limited Product Warranty

Mifare® is a Trademark of NXP Semiconductors

